D3898-1LXX FLOOR PROTECTOR (206L)

NOTES:
1) MATERIAL: SEE TABLE
2) FINISH: NONE
3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
4) UNITS: INCHES UNLESS OTHERWISE NOTED
5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
6) IDENTIFICATION: IDENTIFY WITH DART P/N "D3898-1LXX" PER DART QSI 044 METHOD 6.4
7) WEIGHT: 5.0 lbs

3)	TOOLING: THERMOFORM PER MOLD DT9501 PER DART QSI 022. TRIM PER MOLD MINIMUM THICKNESS: 0.050" EXCEPT AS SHOWN	
"	INIININON THORNESS. 0.030 EXCEPT AS SHOWN	

			
PART NUMBER	DESCRIPTION		
D3898-1L02	F6006 SUEDE/POLISHED 701 BLACK LEXAN SHEET 0.125 THICK (REF DART SPEC MLEX.125-F6006-02)		
D3898-1L08	90318 PROTECT-A-GLAZE 112 CLEAR LEXAN SHEET 0.118 THICK (REF DART SPEC MLEX.118-90318-08)		

		В	D3898-1		NFIGURATION AND RE-IDENTIFIED 3. REVISED NOTE 1 AND ADDED	AK	14.05.30
		Α	NEW IS:	SUE		PH	09.02.27
		REV.			DESCRIPTION	BY	DATE
		DESIGN	7_	AK	DART AEROSPA	CE L	TD
	OVED	DRAWN		RF	HAWKESBURY, ONTARIO, CANADA		
1		CHECKED		VS	DRAWING NO.		REV. B
†		MFG. A	PPR.	DL	D3898		SHEET 1 OF 2
l	PR	APPRO	VED	HS ,,	TITLE		SCALE
4	APF	DE APF	PR.	DS	FLOOR PROTECTOR	(206	L) nts i
	⋖	DATE 14.05.30		5.30	COPYRIGHT © 2009 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.		

